

AD-A132 852

ON A VISCOMETRIC FLOW OF A SIMPLE FLUID(U) WISCONSIN  
UNIV-MADISON MATHEMATICS RESEARCH CENTER K R RAJAGOPAL  
AUG 83 MRC-TSR-2547 DAAG29-80-C-0041

1/1

UNCLASSIFIED

F/G 20/4


NL

END

DATE

FILED

DTIC



MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS - 1963-A

AD-A132852

2

MRC Technical Summary Report #2547

ON A VISCOMETRIC FLOW OF A SIMPLE FLUID

K. R. Rajagopal

Mathematics Research Center  
University of Wisconsin—Madison  
610 Walnut Street  
Madison, Wisconsin 53705

August 1983

(Received July 1, 1983)

DTIC FILE COPY

Approved for public release  
Distribution unlimited

DTIC  
ELECTE

SEP 23 1983

Sponsored by

U. S. Army Research Office  
P. O. Box 12211  
Research Triangle Park  
North Carolina 27709

88 09 22 119

UNIVERSITY OF WISCONSIN-MADISON  
MATHEMATICS RESEARCH CENTER

ON A VISCOMETRIC FLOW OF A SIMPLE FLUID

K. R. Rajagopal\*

Technical Summary Report #2547  
August 1983

ABSTRACT

A class of globally viscometric flows which has relevance to slow flows occurring between two infinite parallel plates rotating with differing angular velocities about a common axis, is studied.

AMS (MOS) Subject Classification: 76A05

Key Words: viscometric flow, simple fluid, motions with constant stretch  
history, Rivlin-Ericksen fluid

Work Unit Number 6 - Miscellaneous Topics

---

\*Department of Mechanical Engineering, University of Pittsburgh, Pittsburgh,  
PA 15261

---

Sponsored by the U. S. Army under Contract No. DAAG29-80-C-0041.

# SIGNIFICANCE AND EXPLANATION

Viscometric flows are locally equivalent to steady simple shear flows and in such flows the behavior of a simple fluid can be completely characterized by three scalar functions of a single variable, namely the shear. Most of the familiar flows in the literature, namely Couette flow, Poiseuille flow, etc., belong to the above class. In this paper we investigate a class of viscometric flows which has relevance to the flows occurring between infinite parallel plates rotating about a common axis with different angular velocities.

Accession For		
NTIS GRA&I	<input checked="" type="checkbox"/>	
DTIC TAB	<input type="checkbox"/>	
Unannounced	<input type="checkbox"/>	
Justification		
By		
Distribution/		
Availability Codes		
and/or		
Dist	Special	
<b>A</b>		



The responsibility for the wording and views expressed in this descriptive summary lies with MRC, and not with the author of this report.

# ON A VISCOMETRIC FLOW OF A SIMPLE FLUID

K. R. Rajagopal\*

## 1. Introduction

In one of his several pioneering papers in the fifties, Rivlin [1] studied the torsional flow between two parallel disks. He considered a velocity field of the form:

$$u = -\psi zy, \quad v = \psi zx \quad \text{and} \quad w = 0, \quad (1)$$

$u$ ,  $v$ , and  $w$  being the velocities in the  $x$ ,  $y$ , and  $z$  directions, respectively. The above motion is viscometric (cf. Pipkin [2]) and has relevance to the low Reynolds number flow between rotating disks. The form (1) corresponds to a flow in which each plane parallel to the plates is rotating as though it were rigid, the angular velocity of these plates varying linearly. However, such a linear variation is by no means the only possible one in the case of a simple fluid.

In this paper, I shall consider a generalization of (1) which is applicable for the slow flow of a simple fluid between parallel plates rotating with differing angular velocities about a common axis (see Fig. 1). The assumed form for the velocity field falls into the category of pseudo-plane motions which were studied by Berker [3].

---

\*Department of Mechanical Engineering, University of Pittsburgh, Pittsburgh, PA 15261




Figure 1.

We shall assume a flow fluid of the form

$$u = -\Omega(z)y, \quad v = \Omega(z)x, \quad w = 0, \quad (2)$$

where  $\Omega(z)$  is an arbitrary function  $z$  which needs to be determined from the equations of motion for the specific fluid under consideration.

After a brief discussion of the basic definitions and notations that we will need, in the next section, we proceed to show that a motion of the form (2) is viscometric. We conclude with an example of a specific fluid model wherein  $\Omega(z)$  need not be linear.

## 2. Preliminaries

Let  $\underline{x}$  denote the position of an element  $\underline{X}$  in the reference state at time  $t$  and let  $\underline{\xi}$  denote the position of  $\underline{X}$  at time  $\tau$ . The dependence of  $\underline{\xi}$  on  $\underline{x}$ ,  $t$  and  $\tau$  can be expressed as

$$\underline{\xi} = \chi(\underline{x}, \tau). \quad (3)$$

The relative deformation gradient  $\underline{F}_t(\tau)$  is then defined through

$$\underline{F}_t(\tau) = \text{grad}_{\underline{x}} \chi_t(\underline{x}, \tau). \quad (4)$$

The relative right Cauchy-Green tensor is defined through

$$\underline{C}_t(\tau) = \underline{F}_t^T(\tau) \underline{F}_t(\tau), \quad (5)$$

the velocity gradient tensor  $\underline{L}(t)$  through

$$\underline{L}(t) = \left. \frac{d}{d\tau} \underline{F}_t(\tau) \right|_{\tau=t}. \quad (6)$$

and the Rivlin-Ericksen tensors (cf. Rivlin and Ericksen [4]) through

$$\underline{A}_1 = \underline{L} + \underline{L}^T, \quad (7)_1$$

$$\underline{A}_n = \frac{d\underline{A}_{n-1}}{dt} + \underline{A}_{n-1}\underline{L} + \underline{L}^T \underline{A}_{n-1}, \quad n=2,3,\dots \quad (7)_2$$

A motion is said to be viscometric\* (cf. Coleman [5]) if at that given material point, the right relative Cauchy-Green tensor can be expressed as



$$\underline{C}_t(t-s) = \underline{1} - s\underline{A}_1 + \frac{s^2}{2} \underline{A}_2, \quad (8)$$

for all  $t$  and if relative to some orthonormal basis  $\hat{\underline{e}}_1$ , the Rivlin-Ericksen tensors have the following matrix representation

$$\underline{A}_1 = \begin{pmatrix} 0 & 0 & \kappa \\ 0 & 0 & 0 \\ \kappa & 0 & 0 \end{pmatrix}, \quad \underline{A}_2 = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 2\kappa^2 \end{pmatrix}, \quad (9), (10)$$

where  $\kappa$  is usually referred to as the "shear rate"

\*We choose to use the above definition for a viscometric flow since we shall find the need to employ the kinematical tensors  $\underline{A}_1$  and  $\underline{A}_2$  used in the above definition, later on. A flow is viscometric (cf. Coleman, Markovitz and Noll [6]) if

$$\underline{F}_t(t-\tau) = \underline{R}(t-\tau)(\underline{1} - (t-\tau)\underline{M}),$$

where  $\underline{R}(t-\tau)$  is orthogonal with  $\underline{R}(0) = \underline{1}$  and  $\underline{M}$  is a tensor which has the following matrix representation with respect to a suitable axis

$$\begin{pmatrix} 0 & 0 & \kappa \\ 0 & 0 & 0 \\ \kappa & 0 & 0 \end{pmatrix}.$$

### 3. The Flow Field

Consider the motion represented by (2), i.e.,

$$u = -\Omega(z)y,$$

$$v = \Omega(z)x, \text{ and}$$

$$w = 0,$$

where  $u$ ,  $v$ , and  $w$  denote the  $x$ ,  $y$ , and  $z$  components of the velocity, respectively. The motion represented by (10) is isochoric. Let us denote by  $\xi$  the 3-tuple  $(\xi, \eta, \zeta)$ . Then (10) implies that

$$\dot{\xi} = -\Omega(\zeta)[\eta], \quad (11)_1$$

$$\dot{\eta} = \Omega(\zeta)[\xi], \quad (11)_2$$

$$\dot{\zeta} = 0. \quad (11)_3$$

with

$$\xi(t) = x, \eta(t) = y, \text{ and } \zeta(t) = z. \quad (12)$$

A straightforward computation yields

$$\xi(\tau) = x \cos[(\Omega(z))(t-\tau)] + y \sin[(\Omega(z))(t-\tau)], \quad (13)_1$$

$$\eta(\tau) = -x \sin[(\Omega(z))(t-\tau)] + y \cos[(\Omega(z))(t-\tau)], \quad (13)_2$$

$$\zeta(\tau) = z \quad (13)_3$$

Thus, the relative deformation gradient has the following matrix representation:

$$\underline{F}_t(\tau) = \begin{pmatrix} \cos[(\Omega(z))(t-\tau)] & \sin[(\Omega(z))(t-\tau)] & -x(t-\tau)\Omega'(z)\sin[(\Omega(z))(t-\tau)] & \\ & & +y(t-\tau)\Omega'(z)\cos[(\Omega(z))(t-\tau)] & \\ -\sin[(\Omega(z))(t-\tau)] & \cos[(\Omega(z))(t-\tau)] & -x(t-\tau)\Omega'(z)\cos[(\Omega(z))(t-\tau)] & \\ & & -y(t-\tau)\Omega'(z)\sin[(\Omega(z))(t-\tau)] & \\ 0 & 0 & 1 & \end{pmatrix} \quad (14)$$

Hence, the right relative Cauchy-Green strain history takes the simple form

$$\underline{C}_t(t-s) = \begin{pmatrix} 1 & 0 & sy(\Omega'(z)) \\ 0 & 1 & -sx(\Omega'(z)) \\ y(\Omega'(z))s & -x(\Omega'(z))s & 1+[(\Omega'(z))s]^2(x^2+y^2) \end{pmatrix} \quad (15)$$

We now proceed to compute the Rivlin-Ericksen tensors  $\underline{A}_n$ . First, it follows from (8), the velocity gradient  $\underline{L}$  is given by

$$\underline{L} = \begin{pmatrix} 0 & -\Omega(z) & -y\Omega'(z) \\ \Omega(z) & 0 & x\Omega'(z) \\ 0 & 0 & 0 \end{pmatrix}. \quad (16)$$

Thus, the first two Rivlin-Ericksen tensors are given by

$$\underline{A}_1 = \begin{pmatrix} 0 & 0 & -y\Omega'(z) \\ 0 & 0 & x\Omega'(z) \\ -y\Omega'(z) & x\Omega'(z) & 0 \end{pmatrix}, \quad (17)$$

and

$$\underline{A}_2 = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 2[(y\Omega'(z))^2 + (x\Omega'(z))^2] \end{pmatrix}. \quad (18)$$

We also provide the matrix representations of  $\underline{A}_1^2$  and  $\underline{A}_1 \underline{A}_2$  which will be useful later on.

$$\underline{A}_1^2 = \begin{pmatrix} [\Omega'(z)y]^2 & -xy(\Omega'(z))^2 & 0 \\ -xy(\Omega'(z))^2 & [x\Omega'(z)]^2 & 0 \\ 0 & 0 & \{[y\Omega'(z)]^2 + [x\Omega'(z)]^2\} \end{pmatrix}. \quad (19)$$

$$\underline{A}_1 \underline{A}_2 = \begin{pmatrix} 0 & 0 & -2[\Omega'(z)]^3 y(x^2 + y^2) \\ 0 & 0 & 2[\Omega'(z)]^3 x(x^2 + y^2) \\ 0 & 0 & 0 \end{pmatrix}. \quad (20)$$

It is easy to verify that the Rivlin-Ericksen tensors  $\underline{A}_1$  and  $\underline{A}_2$  can be expressed in the form (9) and (10) where the new basis  $\hat{\underline{e}}_i$  ( $i=1,2,3$ ) is related to the old cartesian basis  $\underline{e}_i$  ( $i=1,2,3$ ) through

$$\hat{\underline{e}}_1 = \frac{-y\Omega'(z)}{\kappa} \underline{e}_1 + \frac{x\Omega'(z)}{\kappa} \underline{e}_2,$$

$$\hat{\underline{e}}_2 = \frac{-y\Omega'(z)}{\kappa} \underline{e}_2 - \frac{x\Omega'(z)}{\kappa} \underline{e}_1,$$

$$\hat{\underline{e}}_3 = \underline{e}_3,$$

with

$$\kappa = \{[y\Omega'(z)]^2 + [x\Omega'(z)]^2\}^{1/2}.$$

It then follows from equations (15), (17), (18) and the definition of a viscometric flow that the motion (2) under consideration is indeed viscometric. Furthermore, a simple computation yields

$$\hat{A}_n = 0, \quad \forall \quad n > 3.$$

#### 4. Discussion

It is easy to verify by virtue of (17)-(20) that a velocity field of the form (10) given by\*

$$u(x,y,z) = -\left[\frac{(\Omega_2 - \Omega_1)}{h} z + \left(\frac{\Omega_1 + \Omega_2}{2}\right)\right]y ,$$

$$v(x,y,z) = \left[\left(\frac{\Omega_2 - \Omega_1}{h} z + \left(\frac{\Omega_1 + \Omega_2}{2}\right)\right)\right]x ,$$

$$w(x,y,z) = 0 ,$$

satisfies the equation of motion for the non inertial flow of the classical linearly viscous fluid and the Rivlin-Ericksen fluids of second and third grade\*\*. In the case of the linearly viscous fluid the above solution is the unique solution to the "Stokes flow" problem. In the case of the incompressible Rivlin-Ericksen fluids of the second and third grade, the above flow would be the unique solution under certain conditions if the fluids are required to be thermodynamically compatible\*\*\* (cf. Fosdick and Rajagopal [9]).

\* This is Rivlin's [4] result extended to the case when both the top and bottom plates are rotating.

\*\* The stress constitutive equations for the linearly viscous fluid and the incompressible Rivlin-Ericksen fluids of second and third grade are given by (cf. Truesdell and Noll [7]):

$$\underline{T} = -p\underline{1} + \mu \underline{A}_1 ,$$

$$\underline{T} = -p\underline{1} + \mu \underline{A}_1 + \alpha_1 \underline{A}_2 + \alpha_2 \underline{A}_1^2 ,$$

$$\underline{T} = -p\underline{1} + \mu \underline{A}_1 + \alpha_1 \underline{A}_2 + \alpha_2 \underline{A}_1^2 + \beta_1 \underline{A}_3 + \beta_2 [\underline{A}_1 \underline{A}_2 + \underline{A}_2 \underline{A}_1] + \beta_3 (\text{tr} \underline{A}_1^2) \underline{A}_2 .$$

\*\*\* The fluid is said to be thermodynamically compatible if it meets the Clausius-Duhem inequality in all its motions and if the specific Helmholtz free energy is a minimum when the fluid is at rest under isothermal conditions. The uniqueness result is not a consequence of Tanner's theorem [10] as the flow in question is not plane.

However, the flow (2) is by no means the only one possible in a general simple fluid. We give below an example of a simple fluid which is properly frame invariant in which an infinity of solutions is possible for the above problem. Of course, the fluid model may not be a realistic one. It should however be noted that one could easily construct fluid models wherein the stress is expressible as polynomials of the gradients of velocity and the  $(n-1)^{\text{th}}$  accelerations, the class of models studied by Rivlin [1], where non-unique solutions for  $\Omega(z)$  are possible.

Let us consider a fluid model whose Cauchy stress  $\underline{T}$  is given by

$$\underline{T} = -p\underline{1} + \frac{1}{(\text{tr}\underline{A}_1^2)} \underline{A}_2 .$$

Such a fluid model is definitely permissible under the class of simple fluids (cf. Wineman and Pipkin [11]). A trivial computation, for the problem in question, verifies that

$$\frac{1}{(\text{tr}\underline{A}_1^2)} \underline{A}_2 = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 1 \end{pmatrix} .$$

It then follows that any smooth  $\Omega(z)$  which is such that it is  $\Omega_1$  at the top and  $\Omega_2$  at the bottom would be permissible!

Acknowledgement: The author would like to thank Ms. K. Spear for useful discussions.

### Bibliography

- [ 1 ] Rivlin, R.S., Solutions of Some Problems in the Exact Theory of Visco-Elasticity, J. Rational Mech. Anal., 5, 179-187 (1956).
- [ 2 ] Pipkin, A.C., Controllable viscometric flows, Quarterly Appl. Math., 26, 87-100 (1967).
- [ 3 ] Berker, R., Integration des equations du mouvement d'un fluide visqueux, incompressible, Handbuch der Physik, VIII/2, Springer, Berlin-Göttingen-Heidelberg (1963).
- [ 4 ] Rivlin, R.S., Ericksen, J.L., Stress deformation relations for isotropic materials, J. Rational Mech. Anal., 4, 323-425 (1955).
- [ 5 ] Coleman, B.D., Kinematical concepts with applications in the mechanics and thermodynamics of incompressible viscoelastic fluids, Arch. Rational Mech. Anal., 9, 273-300 (1962).
- [ 6 ] Coleman, B.D., Markovitz, H., Noll, W., Viscometric flows of Non-Newtonian fluids, Springer-Verlag, New York (1966).
- [ 7 ] Truesdell, C. Noll, W., The non-linear field theories of mechanics, Flügges Handbuch der Physik, III/3, Springer, Berlin-Heidelberg-New York (1965).
- [ 8 ] Fosdick, R.L., Rajagopal, K.R., Uniqueness and drag for fluids of second grade in steady motion, Intl. J. Non-linear Mechanics, 13, 131-137 (1978).
- [ 9 ] Fosdick, R.L., Rajagopal, K.R., Thermodynamics and Stability of fluids of grade three, Proc. Roy. Soc. London, A 339, 351-377 (1980).
- [10] Tanner, R.I., Plane creeping flows of incompressible second order fluids, Physics of Fluids, 9, 1246-1247 (1966).
- [11] Wineman, A.S., Pipkin, A.C., Material symmetry restrictions on constitutive equations, Arch. Rational Mech. Anal., 17, 184-214 (1964).

KRR/jik



REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER  2547	2. GOVT ACCESSION NO.  AD-A132 852	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle)  ON A VISCOMETRIC FLOW OF A SIMPLE FLUID		5. TYPE OF REPORT & PERIOD COVERED Summary Report - no specific reporting period
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s)  K. R. Rajagopal		8. CONTRACT OR GRANT NUMBER(s)  DAAG29-80-C-0041
9. PERFORMING ORGANIZATION NAME AND ADDRESS Mathematics Research Center, University of 610 Walnut Street Madison, Wisconsin 53706		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Work Unit Number 6 - Miscellaneous Topics
11. CONTROLLING OFFICE NAME AND ADDRESS U. S. Army Research Office P.O. Box 12211 Research Triangle Park, North Carolina 27709		12. REPORT DATE August 1983
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 11
		15. SECURITY CLASS. (of this report)  UNCLASSIFIED
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  viscometric flow, simple fluid, motions with constant stretch history, Rivlin-Ericksen fluid.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  A class of globally viscometric flows which has relevance to slow flows occurring between two infinite parallel plates rotating with differing angular velocities about a common axis, is studied.		